
# **STRATUM**

# IP54 Recessed downlights







150

## 101STR.1.02-R881



**IK05** 850°









lmax=1862 Cd

700

1050

1400

η=100.0% ▼M ▼Ø ▼LUX

2 2.5

3 3.7 207

4 4.9 116

5 6.1 74

1.23 1862

465



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 150mm.

Protection rating against dust and moisture: IP54 from underneath.

White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.

Intermediate tempered frosted glass.

Remote driver supplied.

Electronic options for lighting control: DALI-2. 3 hours battery available as option (class I).

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted by spring clamps for easy installation.

Luminaire luminous flux: 3900lm Luminaire connected power: 700 W Luminaire efficiency: 59 lm/W Light source luminous flux: D Light source power: 25.33 W Constant Current: 2700 mA

CRI: 1

Colour Temperature: >80 **Chromaticity Tolerance: 91** 

Beam Angle: 63° **LOR:** 2301%

Average Service Life: 50000h Photobiological safety group: 50000

This product contains a light source of energy efficiency class 23

#### **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC + looping through) D: DALI-2/switchDIM/corridorFUNCTION + Battery 3h

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.05.2024]

5 years guarantee



Spain

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13