

108TOP.1.02-I637



Pendant downlights with symmetrical light distribution to achieve an effective ambient lighting.
Circular design in 350mm diameter.
Powder painted aluminium profile available in assorted finishes, customized RAL under request.
PMMA opal diffuser (thickness 3mm.)
Tridonic high energy efficiency printed circuit board.
Built-in driver, included.

Electronic options for lighting control: DALI-2 .

Passive temperature management: heat dissipation flows through the fixture body itself.

Delivered with a short powder painted metal rod, custom made length up to 1000mm, minimum 300mm.

Mounted to the ceiling by cylindrical ceiling rose.

TOP can be combined with the LEDA surface-mounted fixtures and KUU and CANDRA recessed mounted lines to get an harmonious finish.

Luminaire luminous flux: 2262lm

Luminaire connected power: 18.14 W

Luminaire efficiency: 125 lm/W

Light source luminous flux: 2600lm

Light source power: 17 W

Constant Current: 600 mA

CRI: >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 114°

LOR: 87%

Average Service Life: 50000h

LED reliability: >50000 L90B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.45m

Photobiological safety group: 1

Cd/Klm: 345

Imax: 780 Cd

This product contains a light source of energy efficiency class C

Electronic Equipment


S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 01.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12
T. +34 93 881 37 13

info@rovasi.com

www.rovasi.com