



101TNS.1-R939



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Round design in diameter 55mm.

Aluminium trim powder painted in various finishes, customized RAL under request.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].

Remote driver included.

Passive temperature management: heat dissipation via aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 500lm

Luminaire connected power: 5.45 W

Luminaire efficiency: 92 lm/W

Light source luminous flux: 735lm

Light source power: 4.9 W

Constant Current: 150 mA

CRI: >90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17°

LOR: 68%

Average Service Life: 50000h

LED reliability: >53000h L80B50

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.55m

Photobiological safety group: 1

Cd/Klm: 5192

This product contains a light source of energy efficiency class E

Electronic Equipment


S: On/Off

D: DALI-2/switchDIM


*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**