

102CNS.1-R942



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design with conical trim in diameter 70mm.

Powder painted aluminium trim available in assorted finishes, customized RAL under request.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].

Remote driver included.

Electronic options for lighting control: DALI-2.

3 hours battery available as option*.

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 606lm

Luminaire connected power: 7.4 W

Luminaire efficiency: 82 lm/W

Light source luminous flux: 865lm

Light source power: 6.7 W

Constant Current: 200 mA

CRI: >90

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 28°

LOR: 70%

Average Service Life: 50000h

LED reliability: >51000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.65m

Photobiological safety group: 1

Cd/Klm: 2910

This product contains a light source of energy efficiency class E

Electronic Equipment

K: On/Off (basic)

S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h

D: DALI-2/switchDIM/corridorFUNCTION


DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi


*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com