

QUADRATIC SHALLOW



Recessed downlights







101QSH.1-R873

Square design available in 225mm x 225mm.

Remarkable low height: 64mm.

general lighting.



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or

Protection rating against dust and moisture: IP54 from underneath. High-purity matt anodised aluminium reflector. Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. Sandblasted flush glass diffuser. Remote driver included. Electronic options for lighting control: DALI-2. 3 hours battery available as option (class I). Passive temperature management: heat dissipation through heat sink diffuser. Ceiling-mounted using galvanised steel support with spring clamps. Luminaire luminous flux: 1652lm Imax=805 Cd η=100.0% ▼M ▼Ø ▼LUX 86° Luminaire connected power: 18.33 W 1 1.86 805 Luminaire efficiency: 90 lm/W 150 2 3.7 201 Light source luminous flux: 2430lm 300 Light source power: 17 W 3 5.6 89 450 Constant Current: 500 mA 4 7.4 50 **CRI:** >90 Colour Temperature: 3000K 5 9.3 32 Chromaticity Tolerance: MacAdam 3 Beam Angle: 86° LOR: 68% Average Service Life: 50000h LED reliability: 50000h L90B10 UGR: >22 Photobiological safety group: 1

Imax: 805 Cd This product contains a light source of energy efficiency class E

Electronic Equipment

Cd/Klm: 487

K: On/Off (basic) S: On/Off (AC/DC + looping through) SE: On/Off (AC/DC+looping) + 3h battery D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h B: Bluetooth-Casambi

*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.05.2024]

5 years guarantee BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

T. +34 93 881 35 12 T. +34 93 881 37 13

Contact

info@rovasi.com www.rovasi.com