

# WATERTIGHT SQ

IP65 Recessed downlights

**ROVASI**  
Positive Lighting



102WSQ.8.01-I872



Recessed ceiling-mounted downlight with symmetrical light distribution.  
 Square design in 258mm x 258mm.  
 Protection rating against dust and moisture: entire IP65.  
 Protection rating of resistance to harmful mechanical impacts: IK07.  
 High purity matt anodised aluminium reflector.  
 5mm tempered protection glass clear as standard, other finishes under request.  
 Polycarbonate diffuser as option to achieve IK10 protection degree.  
 Die-cast aluminium body treated against corrosion and coated with polyester powder painting.  
 Frame made of 316L stainless steel marine grade.  
 A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0258+F2.A1].  
 Temperature resistant silicone rubber gasket.  
 IP67 venting valve to reduce condensation.  
 Built-in driver, included.  
 Electronic options for lighting control: DALI-2.  
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits:  $PstLM \leq 1$  and  $SVM \leq 0.4$ .  
 Passive temperature management: heat dissipation flow through the fixture body itself.  
 Mounted to the ceiling by four fixing points, ceiling thickness up to 20mm.  
 Pre-wiring of 35cm cable 3x1mm<sup>2</sup>.  
 IP68 connector to be ordered separately [reference F3.A3 (On/Off) / F3.A5 (DALI)].

**Luminaire luminous flux:** 1322lm  
**Luminaire connected power:** 18.33 W  
**Luminaire efficiency:** 72 lm/W  
**Light source luminous flux:** 2280lm  
**Light source power:** 17 W  
**Constant Current:** 500 mA  
**CRI:** >90  
**Colour Temperature:** 2700K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 58°  
**LOR:** 58%  
**LED reliability at nominal Ta = 25°C:** 50000h L90B10  
**Photobiological safety group:** 1  
**Cd/Klm:** 647  
**Imax:** 1475 Cd

**This product contains a light source of energy efficiency class E**

## Electronic Equipment


**S:** On/Off  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**B:** Bluetooth-Casambi [ 15m ]

\*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

## Finishes

**8:** Stainless Steel 316L: Marine grade, **1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

## Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.06.2025]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
 BSI Cert ISO 14001:2015 - n°EMS 554685

## ROVASI S.L.

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

## Contact

T. +34 93 881 35 12 info@rovasi.com  
 T. +34 93 881 37 13 **www.rovasi.com**