

PRISMA

Surface mounted downlights









101PSM.1-I874







Surface-mounted downlight with symmetrical light distribution to achieve an effective task or ambient

Neutral cubic body in dimensions 225mm x 225mm.

High purity matt anodised aluminium reflector.

Powder painted aluminium body available in assorted finishes, customized RAL under request.

Flush decorative glass available as accessory.

Drop glass accessory available in assorted colours [reference M1.C0225].

Drop metal square accessory available in assorted colours [reference M1.E0225].].

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture

Imax=1745 Cd

600

900

1200

η=82.5% ▼ M ▼ Ø ▼LUX

1.45 1745

109

1

2 2.9 436

3

4 5.8

5 7.3 70 72°

Mounting to the ceiling plate with two securing points. Cable entry from the top of the fixture.

Luminaire luminous flux: 2091lm Luminaire connected power: 18.33 W Luminaire efficiency: 114 lm/W Light source luminous flux: 2550lm

Light source power: 17 W Constant Current: 500 mA

CRI: >90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 72° **LOR:** 82%

Average Service Life: 50000h LED reliability: 50000h L90B10

UGR: <19

Photobiological safety group: 1

Cd/Klm: 684 **Imax:** 1744 Cd

This product contains a light source of energy efficiency class E

Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13