Recessed downlights



▼Ø ▼LUX

0.93 4102

1.87 1025

4.7 164


1


2

3 2.8 456

4 3.7 256







101QID.1-R876



IP20













Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 150mm.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Glass accessory available to increase the protection rating to IP54 from underneath[reference M2.K0150].

Remote driver supplied. Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 2916lm Luminaire connected power: 26.2 W Luminaire efficiency: 111 lm/W Light source luminous flux: 3940lm Light source power: 24 W

Constant Current: 700 mA **CRI:** >80 Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 50°

LOR: 74%

Average Service Life: 50000h LED reliability: 50000h L90B10

UGR: <16 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m

Photobiological safety group: 1

Cd/Klm: 1042 Imax: 3673 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -K, -D, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.04.2024]

5 years guarantee



Spain