

Recessed downlights









101QID.1-R877



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 150mm.


Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Glass accessory available to increase the protection rating to IP54 from underneath[reference M2.K0150].

Remote driver supplied. Electronic options for lighting control: DALI-2. Passive temperature management: heat dissipation flows through aluminium heat sink. Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 3038lm Luminaire connected power: 26.2 W Luminaire efficiency: 116 lm/W Light source luminous flux: 4105lm Light source power: 24 W Constant Current: 700 mA **CRI:** >80 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 50° LOR: 74% Average Service Life: 50000h LED reliability: 50000h L90B10 UGR: <16 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m Photobiological safety group: 1 Cd/Klm: 1042 Imax: 4413 Cd



This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi

*Add the suffix -K, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com