Recessed downlights



▼Ø ▼LUX

0.70 2825

3.5 113

706 1.40


1


2

3 2.1 314

4 2.8 177







103QID.1-R865



IP20













Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 190mm.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Glass accessory available to increase the protection rating to IP54 from underneath [reference M2.K01901

Remote driver supplied. Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 1658lm Luminaire connected power: 12.61 W Luminaire efficiency: 131 lm/W Light source luminous flux: 2125lm Light source power: 11 W

Constant Current: 350 mA **CRI:** >80 Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 39°

LOR: 78%

Average Service Life: 50000h LED reliability: 50000h L90B10

UGR: <16

Photobiological safety group: 1

Cd/Klm: 1329 Imax: 2824 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic) **D:** DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -K, -D, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 T. +34 93 881 37 13