

# ACTIVO

## Adjustable recessed downlights









### 101ACT.1-R867

















lmax=15731 Cd

η=90.7% ▼ M ▼ Ø ▼ LUX

2

3

4 0.86 983

0.22 15731

0.43 3933

0.65 1748

1.08 629

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Adjustable to 20°.

Circular design in diameter 160mm.

Aluminium reflector in assorted finishes: facetted metalized or sandblasted metalized depending on the beam angle outcome.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. Remote driver supplied.

Electronic options for lighting control: DALI-2.

3 hours battery available as option (class I).

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser. Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 40mm.

Luminaire luminous flux: 1574lm Luminaire connected power: 12.61 W Luminaire efficiency: 125 lm/W Light source luminous flux: 1730lm

Light source power: 11 W Constant Current: 350 mA

**CRI:** >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12° **LOR:** 91%

Average Service Life: 50000h LED reliability: 50000h L90B10

**UGR:** <16

Photobiological safety group: 1

**Cd/Klm:** 9093 Imax: 15731 Cd

This product contains a light source of energy efficiency class  $\mbox{\ensuremath{\mathbb{E}}}$ 

#### **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC + looping through) **SE:** On/Off (AC/DC+looping) + 3h battery **D:** DALI-2/switchDIM/corridorFUNCTION

**DE:** DALI-2/switchDIM/corridorFUNCTION + Battery 3h

B: Bluetooth-Casambi

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



Spain