
# Surface mounted downlights









## 143GTA.1-I908



IP20 850°





Surface mounted downlights with symmetrical light distribution to achieve an effective task or general

Neutral cylindrical body in diameter 60mm.

Sandblasted metalized aluminium reflector silver finished.

Powder painted aluminium profile available in assorted finishes, customized RAL under request.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

lmax=939 Cd

450

600

η=100.0% ▼ M ▼ Ø ▼ LUX

1

2 1.48 235

4 3.0 59

0.74 939

3.7 38 41°

Mounting to the ceiling plate with two securing points. Cable entry from the top of the fixture. GOTA can be combined with the KERI pendant line to get a harmonious finish.

Luminaire luminous flux: 483lm Luminaire connected power: 5.32 W Luminaire efficiency: 91 lm/W Light source luminous flux: 690lm Light source power: 4.8 W Constant Current: 150 mA

**CRI:** >90

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 41°

**LOR:** 70%

Average Service Life: 50000h LED reliability: 50000h L90B10

**UGR:** <16

Photobiological safety group: 1

This product contains a light source of energy efficiency class  $\[ \]$ 

#### **Electronic Equipment**

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

#### **Finishes**

1: RAL9010: Pure White textured, 2: RAL9005: Jet Black textured, 4: RAL7016: Anthracite Grey textured, 7: RAL9006: White Aluminium textured

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASIS.L.**

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13