
# Pendant downlights









## 137KER.1-I909



IP20 850°







Pendant downlights with symmetrical light distribution to achieve an effective task or general lighting. Neutral cylindrical body in diameter 60mm.

Sandblasted metalized aluminium reflector silver finished.

Powder painted aluminium profile available in assorted finishes, customized RAL under request. Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Delivered with 1 meter steel cord as standard. Transparent electronic wire. Mounted to the ceiling by cylindrical ceiling rose.

For a more dynamic result, it can be supplied with an adapter for three-phase track [reference M3.A]. KERI can be combined with the GOTA surface mounted downlights line fixtures to get a harmonious finish.

Imax=1761 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

1

2 0.77 438

4

5 1.92 70

0.38 1754

1.15

1.53 110 22°

Luminaire luminous flux: 425lm Luminaire connected power: 5.32 W Luminaire efficiency: 80 lm/W Light source luminous flux: 720lm Light source power: 4.8 W Constant Current: 150 mA

**CRI:** >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 22° **LOR:** 59%

Average Service Life: 50000h LED reliability: 50000h L90B10

**UGR:** <16

Photobiological safety group: 1

This product contains a light source of energy efficiency class  $\[ \]$ 

#### **Electronic Equipment**

S: On/Off (AC/DC)

**D:** DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

#### **Finishes**

1: RAL9010: Pure White textured, 2: RAL9005: Jet Black textured, 4: RAL7016: Anthracite Grey textured, 7: RAL9006: White Aluminium textured

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13