# RAINA 600 IP40 Wall-mounted linear fixtures





### 651RNA.1-I729



Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 569mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser. Highly efficient linear printed circuit board.

Built-in driver, included.


Electronic options for lighting control: DALI-2.


Passive temperature management.

Wall mounted by mounting brackets.

End caps must be ordered separately, reference M5.E0055.

It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.U.








M5.E0055

M5.U

Luminaire luminous flux: 573lm Luminaire connected power: 7.1 W Luminaire efficiency: 81 lm/W Light source luminous flux: 1080lm Light source power: 6 W Constant Current: 150 mA **CRI:** 90 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 103° LOR: 60% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.35mPhotobiological safety group: 1



#### **Electronic Equipment**

S: On/Off D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

This product contains a light source of energy efficiency class D

#### Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 30.04.2024]

## 5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASI S.L.**

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

#### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com