RAINA 600 IP40 Wall-mounted linear fixtures







569






M5.E0055

M5.U

651RNA.1-I730



Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 569mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser. Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.


Passive temperature management.

Wall mounted by mounting brackets.

End caps must be ordered separately, reference M5.E0055.

It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.U.

Luminaire luminous flux: 1007lm Luminaire connected power: 12.08 W Luminaire efficiency: 83 lm/W Light source luminous flux: 1900lm Light source power: 11 W Constant Current: 250 mA **CRI:** 80 Colour Temperature: 2700K Chromaticity Tolerance: MacAdam 3 Beam Angle: 103° LOR: 60% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.45m Photobiological safety group: 1 This product contains a light source of energy efficiency class D



Electronic Equipment

S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi

*Add the suffix -S. -D. -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

T. +34 93 881 35 12 T. +34 93 881 37 13

Contact

info@rovasi.com www.rovasi.com