

RAINA 800 **IP40** Projectors








851RNA.1-I733



Linear projectors with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 569mm length and in a width of 55mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling or wall installation with adjustable fixing brackets.

Luminaire luminous flux: 1085lm Luminaire connected power: 12.08 W Luminaire efficiency: 90 lm/W Light source luminous flux: 2050lm Light source power: 11 W Constant Current: 250 mA CRI: 80 Colour Temperature: 5000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 103° LOR: 60% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: 19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70%



Photobiological safety group: 1 This product contains a light source of energy efficiency class C

Electronic Equipment

Luminaire spacing = 0.45m

S: On/Off D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.04.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com