FLOCCUS

Surface mounted downlights







101FLC.1.02-I868



IK05 IP54 850°







Surface-mounted downlight with symmetrical light distribution to achieve an effective task or ambient

Neutral cylindrical body in diameter 150mm.

Protection rating against dust and moisture: complete IP54.

White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option. Powder painted aluminium body available in assorted finishes, customized RAL under request.

Intermediate tempered frosted glass.

Integral driver supplied.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through aluminium heat sink and the fixture

lmax=877 Cd

450

η=100.0% ▼M ▼Ø ▼LUX

2

3 3.9 97

4 5.1

5 6.4 35

1.28 877

2.6 219

Mounting to the ceiling plate with two securing holes. Cable entry from the top of the luminaire.

Luminaire luminous flux: 1815lm Luminaire connected power: 350 W Luminaire efficiency: 59 lm/W Light source luminous flux: E Light source power: 12.61 W Constant Current: 4000 mA

CRI: 1

Colour Temperature: >90 **Chromaticity Tolerance: 85**

Beam Angle: 63° **LOR:** 1071%

Average Service Life: 50000h Photobiological safety group: 50000

Imax: 19 Cd

This product contains a light source of energy efficiency class 11

Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13