
# KAUTTA 800 IP40 Projectors



78

104



## 831KTA.1-I728



Linear projectors with symmetrical light distribution to achieve an effective accent, task or general lighting.

Linear fixture in 568mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optics for controlling and directing the light.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.


Ceiling or wall installation with adjustable fixing brackets.

Other options available: Recessed.

Frameless recessed. Surface-mounted.

Pendant. Wall-mounted.

Luminaire luminous flux: 964lm Luminaire connected power: 7.1 W Luminaire efficiency: 136 lm/W Light source luminous flux: 1035lm Light source power: 6 W Constant Current: 150 mA CRI: 90 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 43° LOR: 93% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 Photobiological safety group: 1



Imax: 729 Cd This product contains a light source of energy efficiency class D

#### Electronic Equipment

Cd/Klm: 704

S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

#### Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.05.2024]

Spain

# 5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 ROVASI S.L. Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

08540 Centelles | Barcelona

### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

