

KAUTTA 800

IP40 Projectors









833KTA.1-I751



IP40 650°



Linear projectors with symmetrical light distribution to achieve an effective accent, task or general

Linear fixture in 848mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Imax=1233 Cd

η=93.4% ▼ M ▼ Ø ▼ LUX

2 1.58 308

3

4 3.2 77

0.79 1232

3.9 49

137 2.4

43°

PMMA optics for controlling and directing the light.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling or wall installation with adjustable fixing brackets.

Other options available:

Recessed.

Frameless recessed.

Surface-mounted.

Pendant.

Wall-mounted.

Luminaire luminous flux: 1627lm Luminaire connected power: 10.66 W Luminaire efficiency: 153 lm/W Light source luminous flux: 1750lm

Light source power: 10 W Constant Current: 150 mA

CRI: 80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 43° **LOR:** 93%

Average Service Life: 50000h LED reliability: >60000h L80B10 **UGR:** <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m

Photobiological safety group: 1

Cd/Klm: 704 Imax: 1231 Cd

This product contains a light source of energy efficiency class $\, \mathsf{D} + \mathsf{C} \,$

Electronic Equipment

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 30.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

Spain

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com