

KAUTTA 800 IP40 Projectors







833KTA.1-I754



Linear projectors with symmetrical light distribution to achieve an effective accent, task or general lighting.

Linear fixture in 848mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optics for controlling and directing the light. Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.


Ceiling or wall installation with adjustable fixing brackets.

- Other options available:
- Recessed.

Frameless recessed. Surface-mounted. Pendant.

Wall-mounted.

Luminaire luminous flux: 1755lm Luminaire connected power: 10.66 W Luminaire efficiency: 165 lm/W Light source luminous flux: 1885lm Light source power: 10 W Constant Current: 150 mA CRI: 80 Colour Temperature: 5000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 43° LOR: 93% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters



Cd/Klm: 704 Imax: 1328 Cd This product contains a light source of energy efficiency class C

Electronic Equipment

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m

S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi

Photobiological safety group: 1

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.05.2024]

5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L. Ronda de la Font Grossa, 15

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12

T. +34 93 881 35 12 info@rovasi.com T. +34 93 881 37 13 **www.rovasi.com**