



TIRET 100

IP40 Recessed linear downlights

ROVASI
Positive Lighting



159TRT.1-I636



Recessed linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 2806mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal extruded polycarbonate diffuser.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included. Tunable White: 2700K - 6500K.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \leq 1$ and $SVM \leq 0.4$.

3 hours battery available as option.

Passive temperature management.

Ceiling-mounted using galvanized steel support with screws.

It is possible to combine different lengths and junction modules in different ways to create customized systems.

Luminaire luminous flux: 8700lm

Luminaire connected power: 154 W

Light source luminous flux: 15000lm

Light source power: 154 W

CRI: >90


Colour Temperature: 2700K - 6500K

Beam Angle: 84°

Average Service Life: 50000h

Photobiological safety group: 1

This product contains a light source of energy efficiency class F



Electronic Equipment


T: Tunable White DALI-2/switchDIM/ColourSwitch

*Add the suffix **-T** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 13.05.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**