TIRET 200

IP40 Frameless recessed linear downlights





255TRT.1-I616
















Linear fixture in 1126mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal extruded polycarbonate diffuser.

Highly efficient linear printed circuit board. Accessories available to create customized linear systems.

Built-in driver, included. Tunable White: 2700K - 6500K.

Electronic options for lighting control: DALI-2.


3 hours battery available as option.

Passive temperature management.

Ceiling-mounted using galvanized steel support with screws.

It is possible to combine different lengths and junction modules in different ways to create customized





Light source power: 48.1 W

CRI: >90

Colour Temperature: 2700K - 6500K

Beam Angle: 84°

Average Service Life: 50000h Photobiological safety group: 1

This product contains a light source of energy efficiency class F

lmax=1580 Cd η=99.9% ▼ M ▼ Ø ▼ LUX 1.79 1580 2 3.6 395 3 176 5.4 4 7.1 1200

Electronic Equipment

T: DALI-2/switchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



Spain

T. +34 93 881 37 13