


TIRET 200

IP40 Frameless recessed linear downlights



251TRT.1-I726



Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.
Frameless linear fixture in 566mm length and in a width of 40mm.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
Opal extruded polycarbonate diffuser.
Highly efficient linear printed circuit board.
Accessories available to create customized linear systems.
Built-in driver, included.
Electronic options for lighting control: DALI-2.
Passive temperature management.
Ceiling-mounted using steel support with screws.
Pre-wiring of 35cm cable 3x1mm².
It is possible to combine different lengths and junction modules in different ways to create customized systems.

Luminaire luminous flux: 794lm
Luminaire connected power: 7.1 W
Luminaire efficiency: 112 lm/W
Light source luminous flux: 1260lm
Light source power: 6 W
Constant Current: 150 mA
CRI: 80
Colour Temperature: 5000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 91°
LOR: 63%
Average Service Life: 50000h
LED reliability: >72000h L80B10
UGR: <19 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.55m
Photobiological safety group: 1
Cd/Klm: 443
Imax: 558 Cd

This product contains a light source of energy efficiency class C


Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi


*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com