


# TIRET 300

IP40 Surface mounted linear downlights



351TRT.1-I728



IP40


650°



1.84Kg

Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.  
Linear fixture in 566mm length and in a width of 40mm.  
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.  
Opal extruded polycarbonate diffuser.  
Highly efficient linear printed circuit board.  
Accessories available to create customized linear systems.  
Built-in driver, included.  
Electronic options for lighting control: DALI-2.  
Passive temperature management.  
Ceiling-mounted using cleats.  
It is possible to combine different lengths and junction modules in different ways to create customized systems.

**Luminaire luminous flux:** 655lm  
**Luminaire connected power:** 7.1 W  
**Luminaire efficiency:** 92 lm/W  
**Light source luminous flux:** 1040lm  
**Light source power:** 6 W  
**Constant Current:** 150 mA  
**CRI:** 90  
**Colour Temperature:** 3000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 91°  
**LOR:** 63%  
**Average Service Life:** 50000h  
**LED reliability:** >72000h L80B10  
**UGR:** <19 under the below indicated parameters  
Room dimensions X=4H/8H  
Reflectance 20% | 50% | 70%  
Luminaire spacing = 0.45m  
**Photobiological safety group:** 1  
**Cd/Klm:** 443  
**This product contains a light source of energy efficiency class D**



#### Electronic Equipment



**S:** On/Off (AC/DC)  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**B:** Bluetooth-Casambi

\*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

#### Finishes

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12    info@rovasi.com  
T. +34 93 881 37 13    [www.rovasi.com](http://www.rovasi.com)