


TIRET 600 IP40 Wall-mounted linear fixtures









651TRT.1-I723



Wall-mounted linear downlights or uplights with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 566mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal extruded polycarbonate diffuser.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.


Passive temperature management.

Wall mounted by mounting brackets.

It is possible to combine different lengths and junction modules in different ways to create customized systems.

Luminaire luminous flux: 735lm Luminaire connected power: 7.1 W

Luminaire efficiency: 104 lm/W Light source luminous flux: 1165lm Light source power: 6 W Constant Current: 150 mA **CRI:** 80 Colour Temperature: 2700K Chromaticity Tolerance: MacAdam 3 Beam Angle: 91° LOR: 63% Average Service Life: 50000h LED reliability: >72000h L80B10 UGR: 19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.45m Photobiological safety group: 1 Cd/Klm: 443 Imax: 517 Cd



This product contains a light source of energy efficiency class $\ensuremath{\mathbb{D}}$

Electronic Equipment

S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.05.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

S.L.

T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Spain

Contact