HORIZON 200



IP20 Frameless recessed linear downlights

| | 221HRN.1-1978 |
|---|---|
| | IP20 650° +RAL IP20 650° IP20 650° |
| | Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Frameless linear fixture in 576mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. |
| | Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized design. |
| | Luminaire luminous flux: 1775lm Imax=3657 cd ŋ=100.0% V M V Ø VLUX 31° |
| 576 | Luminaire connected power: 13.88 W Luminaire efficiency: 128 Im/W |
| | Light source luminous flux: 1830lm |
| | Light source power: 10 W |
| | Constant Current: 350 mA CRI: 80 |
| | Colour Temperature: 5000K 5 2.8 146 |
| | Chromaticity Tolerance: MacAdam 3 |
| | Beam Angle: 31° LOR: 97% |
| | Average Service Life: 50000h |
| 4 | LED reliability: >54000h L80B10 |
| ۶ <u>ــــــــــــــــــــــــــــــــــــ</u> | UGR: <19 Photobiological safety group: 1 |
| 576 | Cd/Kim: 2060 |
| | Imax: 3770 Cd |
| | This product contains a light source of energy efficiency class C |
| | Electronic Equipment S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi |
| | *Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. |
| | Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | Upgradeable, Replaceable, Repairable |
| | |

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.05.2024]

5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Ronda de la Font Grossa, 15 T. +34 Pol. Ind. La Gavarra T. +34 08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com