HORIZON 200



IP20 Frameless recessed linear downlights

	281HRN.1-1988
	IP20 650° +RAL Image: state sta
	Recessed ceiling mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting. Linear frameless fixture in 576mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optic to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized design.
576	Luminaire luminous flux: 2897 lm Luminaire connected power: 23.25 W Luminaire efficiency: 125 lm/W Light source luminous flux: 3490 lm Light source power: 20 W Constant Current: 700 mA CRI: 80 Colour Temperature: 5000 K Chromaticity Tolerance: MacAdam 3 Beam Angle: ASY° LOR: 83%
⁴ []50 576	Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1 Cd/KIm: 974 Imax: 3399 Cd
	This product contains a light source of energy efficiency class C Electronic Equipment S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi
	*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 09.05.2024]

5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com