# HORIZON 100

## IP20 Recessed linear downlights









### 121HRN.1-I977













max=3597 Cd

η=100.0% ▼M ▼Ø ▼LUX

2 1.11 899

3

0.56 3597

1.67 400

2.2 225

Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 602mm length and in a width of 78mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted using steel support with spring clamps for easy installation...

Pre-wiring of 35cm cable 3x1mm2.

It is possible to combine different lengths and junction modules in different ways to create customized

Luminaire luminous flux: 1746lm Luminaire connected power: 13.88 W Luminaire efficiency: 126 lm/W Light source luminous flux: 1800lm

Light source power: 10 W Constant Current: 350 mA

**CRI:** 80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 31° **LOR:** 97%

Average Service Life: 50000h LED reliability: >54000h L80B10

**UGR:** <19

Photobiological safety group: 1

Cd/Klm: 2060 Imax: 3708 Cd

This product contains a light source of energy efficiency class C

### **Electronic Equipment**

S: On/Off (AC/DC)

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

### **ROVASI S.L.**

### Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13