

181HRN.1-I978



Recessed ceiling mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting.
 Linear fixture in 602mm length and in a width of 78mm.
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
 PMMA optic to achieve specific photometric results.
 Highly efficient linear printed circuit board.
 Accessories available to create customized linear systems.
 Built-in driver, included.
 Electronic options for lighting control: DALI-2.
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4 .
 Passive temperature management.
 Ceiling-mounted using steel support with spring clamps for easy installation..
 Pre-wiring of 35cm cable 3x1mm².
 It is possible to combine different lengths and junction modules in different ways to create customized design.

Luminaire luminous flux: 1519lm
Luminaire connected power: 13.88 W
Luminaire efficiency: 109 lm/W
Light source luminous flux: 1830lm
Light source power: 10 W
Constant Current: 350 mA
CRI: 80
Colour Temperature: 5000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: ASY°
LOR: 83%
Average Service Life: 50000h
LED reliability: >54000h L80B10
Photobiological safety group: 1
Cd/Klm: 974
Imax: 1782 Cd

This product contains a light source of energy efficiency class C


Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi


*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 11.05.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
 T. +34 93 881 37 13 www.rovasi.com