
HORIZON 300

IP20 Surface mounted linear downlights









351HRN.1-I976



IP20







Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Passive temperature management. Ceiling-mounted using cleats.

It is possible to combine different lengths and junction modules in different ways to create customized design.

lmax=1083 Cd

400

η=100.0% ▼ M ▼ Ø ▼LUX

2 3.2 228

4 6.4

5 8.0 36

1.61 911

4.8 101 78°

Luminaire luminous flux: 1546lm Luminaire connected power: 13.88 W Luminaire efficiency: 111 lm/W Light source luminous flux: 1680lm

Light source power: 10 W Constant Current: 350 mA

CRI: 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 78° **LOR:** 92%

Average Service Life: 50000h LED reliability: >54000h L80B10

UGR: <19

Photobiological safety group: 1

Cd/Klm: 698 **Imax:** 1173 Cd

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off (AC/DC)

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13