HORIZON 300



IP20 Surface mounted linear downlights

	381HRN.1-1981	
	IP20 650° +RAL ▲ .22Kg .22Kg	
	Recessed surface mounted linear downlights with as task or accent lighting. Linear fixtures in 576mm length and in a width of 500 Powder painted extruded aluminium profile available PMMA optic to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear sys Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using cleats. It is possible to combine different lengths and junctic design.	mm. in assorted finishes, customized RAL under request. stems.
]65 	Luminaire luminous flux: 1942lm Luminaire connected power: 17.07 W Luminaire efficiency: 114 lm/W Light source luminous flux: 2340lm Light source power: 14 W Constant Current: 500 mA CRI: 80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: ASY° LOR: 83% Average Service Life: 50000h LED reliability: >54000h L80B10	Imax=1882 Cd n=100.0% V M V Ø V LUX 67° 1 1.41 1237 2 2.8 309 700 3 4.2 137 1400 4 5.6 77 1400 5 7.1 49
⁴]50 576	Photobiological safety group: 1 Cd/Klm: 974 Imax: 2279 Cd This product contains a light source of energy Electronic Equipment S: On/Off (AC/DC)	efficiency class C
	 D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi *Add the suffix -S, -D, -B after the reference to indicate your e Finishes 	electronic equipment choice.
	PINISNES 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RA Upgradeable, Replaceable, Repairable $\widehat{(m)} \xrightarrow{(m)}$ $\widehat{(m)} \xrightarrow{(m)}$	L9006: White Aluminium, 1: RAL9010: Pure White
lote		

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.05.2024]

E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com