HORIZON 400

IP20 Pendant linear downlights



η=100.0% ▼M ▼Ø ▼LUX


2 1.11 775

0.56 3099

2.2 194

344 1.67 3







421HRN.1-I980







Pendant linear downlights with symmetrical light distribution to achieve an effective task or general

Linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request.

It is possible to combine different lengths and junction modules in different ways to create customized

Luminaire luminous flux: 1504lm Luminaire connected power: 13.88 W Luminaire efficiency: 108 lm/W Light source luminous flux: 1550lm

Light source power: 10 W Constant Current: 350 mA

CRI: 90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 31° **LOR:** 97%

Average Service Life: 50000h LED reliability: >54000h L80B10

UGR: <19

Photobiological safety group: 1

Cd/Klm: 2060 Imax: 3193 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

T. +34 93 881 37 13