

HORIZON 400

IP20 Pendant linear downlights









481HRN.1-I989



Pendant linear downlights with asymmetrical light distribution to achieve an effective task or accent

2.96Kg

Linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optic to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request.

It is possible to combine different lengths and junction modules in different ways to create customized

max=2291 Cd

η=100.0% ▼M ▼Ø ▼LUX

2 2.8 377

3 4.2

1.41 1506

5.6

167

Luminaire luminous flux: 2366lm Luminaire connected power: 23.25 W Luminaire efficiency: 102 lm/W Light source luminous flux: 2850lm

Light source power: 20 W Constant Current: 700 mA

CRI: 90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: ASY°

LOR: 83%

Average Service Life: 50000h LED reliability: >54000h L80B10

UGR: <19

Photobiological safety group: 1

Cd/Klm: 974 Imax: 2776 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]



Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona

ROVASI S.L.

Spain

Contact T. +34 93 881 35 12

T. +34 93 881 37 13

info@rovasi.com www.rovasi.com