# HORIZON 700

## IP20 Wall-mounted linear fixtures double emission





### 721HRN.1-I980









Wall-mounted linear downlights or uplights with symmetrical light distribution to achieve an effective task or general lighting. Double light emission: up and down.

Linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in Driver, separate switching: up and down.

Electronic options for lighting control: DALI-2 (for downlight position only).

Passive temperature management. Wall mounted by mounting brackets.

It is possible to combine different lengths and junction modules in different ways to create customized design

lmax=3084 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

1

4 2.2

0.56 3084


193

1.12 771

1.68

2.8 123

31°



576

\_\_\_\_\_]50

Luminaire luminous flux: 1504lm Luminaire connected power: 13.88 W Luminaire efficiency: 108 lm/W Light source luminous flux: 1550lm

Light source power: 10 W Constant Current: 350 mA

**CRI:** 90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 31° LOR: 97%

Average Service Life: 50000h LED reliability: >54000h L80B10

**UGR:** <19

Photobiological safety group: 1

**Cd/Klm:** 2060 **lmax:** 3193 Cd

This product contains a light source of energy efficiency class D

## **Electronic Equipment**

D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



BSI Cert ISO 14001:2015 - nºEMS 554685

Spain