# **HORIZON 600**

## IP20 Wall-mounted linear fixtures









### 681HRN.1-I986



IP20 650°





Wall mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent

Linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optic to achieve specific photometric results. Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management. Wall mounted by mounting brackets.

It is possible to combine different lengths and junction modules in different ways to create customized design.

Imax=2581 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

1

2 2.8 424

3

4 5.6

5 7.1 68

1.41 1696

188

106

67°

Luminaire luminous flux: 2664lm Luminaire connected power: 23.25 W Luminaire efficiency: 115 lm/W Light source luminous flux: 3210lm

Light source power: 20 W Constant Current: 700 mA

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: ASY°

**LOR:** 83%

Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1

Cd/Klm: 974 **Imax:** 3127 Cd

This product contains a light source of energy efficiency class C

### **Electronic Equipment**

S: On/Off (AC/DC)

DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 16.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

### **ROVASI S.L.**

Spain

### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com