BARIS 200 IP54 Frameless recessed linear downlights



251BRS.1-I730 +RAL Trive <u>*</u> IK08 IP54 650° 569 x 47mm Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting. Frameless linear fixture in 568mm length and in a width of 44mm. Protection rating against dust and moisture: complete IP54. Protection rating of resistance to harmful mechanical impacts: IK08. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws.Pre-wiring of 35cm cable 3x1mm2. Accessory for serial installation, reference F3.L2.BRS. 78 Luminaire luminous flux: 1007lm Imax=400 Cd Luminaire connected power: 12.08 W Luminaire efficiency: 83 lm/W Light source luminous flux: 1900lm 160 Light source power: 11 W Constant Current: 250 mA 240 **CRI:** 80 Colour Temperature: 2700K Chromaticity Tolerance: MacAdam 3 Beam Angle: 100° LOR: 53% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H]]44 Reflectance 20% | 50% | 70% Luminaire spacing = 0.7m Photobiological safety group: 1 Cd/Klm: 399 Imax: 758 Cd This product contains a light source of energy efficiency class D **Electronic Equipment** S: On/Off D: DALI-2/switchDIM/corridorFUNCTION *Add the suffix -S, -D after the reference to indicate your electronic equipment choice. Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

5 years guarantee

.

568

568

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

Spain

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra T. +34 93 881 37 13 08540 Centelles | Barcelona

Contact

η=100.0% ▼M ▼Ø ▼LUX 100° 1 2.4 399 2 4.8 100 3 7.2 44 25 4 9.6

> 5 12.0 16.0