


651BRS.1-I730



Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.
Linear fixture in 568mm length and in a width of 44mm.
Protection rating against dust and moisture: complete IP54.
Protection rating of resistance to harmful mechanical impacts: IK08.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
Opal polycarbonate diffuser.
Highly efficient linear printed circuit board.
Built-in driver, included.
Electronic options for lighting control: DALI-2.
Passive temperature management.
Wall mounted by mounting brackets.
Accessory for serial installation, reference F3.L6.BRS.

Luminaire luminous flux: 1900lm
Luminaire connected power: 250 W
Luminaire efficiency: 53 lm/W
Light source luminous flux: D
Light source power: 12.08 W
Constant Current: 2700 mA
CRI: 1
Colour Temperature: 80
Chromaticity Tolerance: 83
Beam Angle: 96°
LOR: 1007%
Average Service Life: 50000h
Photobiological safety group: 0
Cd/Klm: 758
This product contains a light source of energy efficiency class 11



Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi

*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com