
BARIS 400

IP54 Pendant linear downlights









451BRS.1-I728



Pendant linear downlights with symmetrical light distribution to achieve an effective task or general

Linear fixture in 568mm length and in a width of 44mm.

Protection rating against dust and moisture: complete IP54.

Protection rating of resistance to harmful mechanical impacts: IK08.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and electrical wire. Different suspension

nax=218 Cd

η=100.0% ▼M ▼Ø ▼LUX

2 4.8 54

3

4 9.6 13.6

2.4 218

12.0

24 7.2

100°

length on request.

Accessory for serial installation, reference F3.L4.BRS.

Luminaire luminous flux: 549lm Luminaire connected power: 7.1 W Luminaire efficiency: 77 lm/W Light source luminous flux: 1035lm

Light source power: 6 W Constant Current: 150 mA

CRI: 90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 100°

LOR: 53%

Average Service Life: 50000h LED reliability: >60000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.55m

Photobiological safety group: 1

Cd/Klm: 399 Imax: 413 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable







LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 13.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com