GOWEL 100 IP20 Recessed linear downlights



	181GWL.1-I776
	IP20 IK06 650° +RAL ▶ Image: S82 x 73mm ▲ 3.12Kg
	Recessed ceiling mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting. Linear fixture in 597mm length and in a width of 84mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optic to achieve specific photometric results. Accessories available to create customized linear systems. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized systems.
₃ _⊧]65 597	Luminaire luminous flux: 4629lm Luminaire connected power: 36.36 W Luminaire efficiency: 127 lm/W
10	Light source luminous flux: 5260lm Light source power: 32 W Constant Current: 500 mA CRI: 80 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: ASY° LOR: 88% Average Service Life: 50000h LED reliability: >54000h L80B10
[]84 597	Photobiological safety group: 1 Cd/KIm: 2131 Imax: 11209 Cd This product contains a light source of energy efficiency class C
	Electronic Equipment S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi
	*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 11.05.2024]

5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com