## GOWEL 100 IP20 Recessed linear downlights



	101GWL.1-I748
	IP20         IK06         650°         +RAL
	Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 597mm length and in a width of 84mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized systems.
3 <u>+ H</u> 597	Luminaire luminous flux: 2776lm Luminaire connected power: 22.35 W
	Luminaire efficiency: 124 lm/W Light source luminous flux: 3050lm Light source power: 19 W Constant Current: 300 mA CRI: 80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 17° LOR: 91%
10 []84	Average Service Life: 50000h LED reliability: >54000h L80B10 UGR: <19 Photobiological safety group: 1
597	Cd/Klm: 6350 Imax: 19368 Cd
	This product contains a light source of energy efficiency class D Electronic Equipment S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION
	<ul> <li>Bluetooth-Casambi</li> <li>*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.</li> </ul>
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.05.2024]

## 5 years guarantee E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## **ROVASI S.L.**

Spain

Pol. Ind. La Gavarra

## Contact Ronda de la Font Grossa, 15 T. +34 93 881 35 12 T. +34 93 881 37 13 08540 Centelles | Barcelona

info@rovasi.com www.rovasi.com