GOWEL 300 IP20 Surface mounted linear downlights



391GWL.1-I769 +RAL IP20 IK06 650° 2.88Kg Surface mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting. Linear fixture in 581mm length and in a width of 70mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optic to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using cleats. It is possible to combine different lengths and junction modules in different ways to create customized systems. Luminaire luminous flux: 4743lm 65 Imax=7424 Cd η=100.0% ▼M ▼Ø ▼LUX 90° Luminaire connected power: 36.36 W 1 1.99 1775 581 Luminaire efficiency: 130 lm/W 2 4.0 444 000 Light source luminous flux: 4890lm 3000 Light source power: 32 W 3 6.0 197 400 Constant Current: 500 mA 4 111 5000 8.0 **CRI:** 80 6000 Colour Temperature: 3000K 5 10.0 71 Chromaticity Tolerance: MacAdam 3 Beam Angle: DASYº LOR: 97% Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1 70 Cd/Klm: 1547 Imax: 7565 Cd 581 This product contains a light source of energy efficiency class D **Electronic Equipment** S: On/Off (AC/DC) DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi *Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. **Finishes** 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White Upgradeable, Replaceable, Repairable $-(LED) \rightarrow \rightarrow (LED)$

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 15.05.2024]

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Contact Ronda de la Font Grossa, 15 T. +34 93 881 35 12 T. +34 93 881 37 13 08540 Centelles | Barcelona

info@rovasi.com www.rovasi.com