SATELLITE

Surface mounted downlights



η=90.9% ▼ M ▼ Ø ▼ LUX

2

3

4 1.69 616


0.42 9864

2.1

0.85 2466

1.27 1096





102STL.1-I869



IP20 850°





Surface-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Neutral cylindrical body in diameter 190mm.

Adjustable to 20° and 180°+180° rotation.

Aluminium reflector in assorted finishes: specular metalized, facetted metalized or sandblasted metalized depending on the beam angle outcome.

Powder painted aluminium body available in assorted finishes, customized RAL under request.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Mounting to the ceiling plate with two securing points.

Cable entry from the top of the fixture.

SATELLITE can be combined with the BASE surface mounted line to get a harmonious finish.

Luminaire luminous flux: 2755lm Luminaire connected power: 500 W Luminaire efficiency: 91 lm/W Light source luminous flux: D Light source power: 18.33 W Constant Current: 2700 mA

CRI: 1

Colour Temperature: >80 Chromaticity Tolerance: 137

Beam Angle: 24° LOR: 2507%

Average Service Life: 50000h Photobiological safety group: 50000

Cd/Klm: 9863

This product contains a light source of energy efficiency class 17

Electronic Equipment

S: On/Off (AC/DC)

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASIS.L.

Spain