
# GOWEL 800

# **IP20 Projectors**







## 801GWL.1-I741











Linear projectors with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 581mm length and in a width of 70mm.

650°

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results.

max=10053 Cd

η=100.0% ▼M ▼Ø ▼LUX

2 0.61 2513

3

4 1.21 628

0.30 10053

0.91 1117

1.51

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling or wall mounted using adjustable supports.

Matching products:

GOWEL 100 recessed with frame. GOWEL 200 frameless recessed. GOWEL 300 surface mounted. GOWEL 400 pendant.

Luminaire luminous flux: 1583lm Luminaire connected power: 11.84 W Luminaire efficiency: 134 lm/W Light source luminous flux: 1740lm

Light source power: 9 W Constant Current: 150 mA

**CRI:** 80

**Colour Temperature:** 5000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17° LOR: 91%

Average Service Life: 50000h LED reliability: >54000h L80B10

**UGR:** <19

Photobiological safety group: 1

**Cd/Klm:** 6350 **lmax:** 11049 Cd

This product contains a light source of energy efficiency class  $\,\mathbb{C}\,$ 

### **Electronic Equipment**

S: On/Off (AC/DC)

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

#### Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685

#### **ROVASIS.L.**

#### Contact

info@rovasi.com www.rovasi.com

T. +34 93 881 35 12 T. +34 93 881 37 13

<sup>\*</sup>Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.