
Minidownlights







110TNS.1-R1083



IP20 850°











Imax=4200 Cd

η=100.0% ▼ M ▼ Ø ▼LUX

1

3 0.92

4 1.23

0.31 4200

0.61 1050

1.53 168

263

17°

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Round design in diameter 55mm.

Aluminium trim powder painted in various finishes, customized RAL under request.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].

Remote driver included.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Passive temperature management: heat dissipation via aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 809lm Luminaire connected power: 9.41 W Luminaire efficiency: 86 lm/W Light source luminous flux: 1190lm

Light source power: 8.5 W Constant Current: 250 mA

CRI: >90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17° **LOR:** 68%

Average Service Life: 50000h LED reliability: >53000h L80B50

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.65m

Photobiological safety group: 1

This product contains a light source of energy efficiency class E

Electronic Equipment

S: On/Off D: DALI-2/switchDIM

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 11.05.2025]

5 years guarantee



Spain