

# HORIZON Soo

## **IP20 Projectors**









### 851HRN.1-I976











Linear projectors with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

Imax=1083 Cd

600

η=100.0% ▼ M ▼ Ø ▼LUX

2 3.2

3 4.8 101

4 6.4 57

1.61 911

8.0

78°

limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4. Passive temperature management.

Ceiling-mounted using adjustable supports.

Matching products:

HORIZON 100 recessed.

HORIZON 300 surface mounted.

HORIZON 400 and HORIZON 500 pendant.

HORIZON 600 and HORIZON 700 wall-mounted.

Luminaire luminous flux: 1546lm Luminaire connected power: 13.88 W Luminaire efficiency: 111 lm/W Light source luminous flux: 1680lm

**Light source power:** 10 W **Constant Current:** 350 mA

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 78° LOR: 92%

Average Service Life: 50000h LED reliability: >54000h L80B10

**UGR:** <19

Photobiological safety group: 1

**Cd/Klm:** 698 **Imax:** 1173 Cd

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

S: On/Off (AC/DC)

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

#### Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 11.05.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685 **ROVASIS.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

e la Font Grossa, 15 T. +34 93