
# SEAL

## IP65 Small recessed downlights



20°





## 124SEL.1.01-R1096











lmax=5011 Cd



η=100.0% ▼ M ▼ Ø ▼ LUX

0.36 5011

0.72 1253

1.07 557

1

2

4 1.43

5 1.79 200

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent

Passive temperature management: heat dissipation flows through an aluminium heat sink. Ceiling-mounted by spring clamps for easy installation.

Luminaire luminous flux: 1333lm Luminaire connected power: 17.05 W Luminaire efficiency: 78 lm/W Light source luminous flux: 1960lm Light source power: 15.4 W Constant Current: 450 mA

**CRI:** >90

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 20° LOR: 68%

Average Service Life: 50000h LED reliability: 50.000h L90B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m

Photobiological safety group: 1

This product contains a light source of energy efficiency class  $\[ \]$ 

#### **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 10.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685

#### **ROVASIS.L.**

#### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com