


101SEL.1.01-R641



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.
Circular design in diameter 87mm.
Protection rating against dust and moisture: IP65 from underneath.
Double trim of die-cast aluminium and flush glass, sealed with a silicone gasket.
Tempered protection glass clear as standard, other finishes under request.
Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.
Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].
Remote driver included.
Electronic options for lighting control: DALI-2.
Passive temperature management: heat dissipation flows through an aluminium heat sink.
Ceiling-mounted by spring clamps for easy installation.

Luminaire luminous flux: 890lm
Luminaire connected power: 9.77 W
Luminaire efficiency: 91 lm/W
Light source luminous flux: 890lm
Light source power: 8.8 W
Constant Current: 250 mA
CRI: >90
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 24°
LOR: 100%
Average Service Life: 50000h
LED reliability: >50000h L70B50
UGR: <16
Photobiological safety group: 1
Cd/Klm: 3767
Imax: 3353 Cd
This product contains a light source of energy efficiency class F



Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery
B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com