


102HDN.1-R649



Recessed ceiling-mounted multidirectional downlights with symmetrical light distribution to achieve an effective task, accent or general lighting.

Square design in 110mm x 110mm.

Swivel mounted downlights, adjustable up to 25° and with 180° rotation.

Die-cast aluminium trim and recessing surface powder painted in assorted finishes, customized RAL under request.

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted with spring clamps for easy installation.

Luminaire luminous flux: 940lm

Luminaire connected power: 11.27 W

Luminaire efficiency: 83 lm/W

Light source luminous flux: 940lm

Light source power: 10 W

Constant Current: 300 mA

CRI: >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 24°

LOR: 100%

Average Service Life: 50000h

LED reliability: >50000h L90B10


UGR: <16

Photobiological safety group: 1

Cd/Klm: 4408

Imax: 4143 Cd

This product contains a light source of energy efficiency class F



Electronic Equipment

K: On/Off (basic)

S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h

D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM + 3h battery



B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 21.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarrà
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com