

CONICAL

Small recessed downlights









102CNC.1-R671



IP20











Imax=3946 Cd





η=100.0% ▼ M ▼ Ø ▼LUX

1

2 0.75 986

3 1.12

4 1.49 247

5 1.87 158

0.37 3946

21°

Recessed ceiling-mounted small downlight with symmetrical light distribution to achieve an effective task or general lighting.

Circular design in diameter 85mm.

850°

Powder painted aluminium conical trim available in assorted finishes, customized RAL under request. Accessory available to increase the protection rating to IP44 from underneath [reference M2.H0085].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Remote driver included.

Electronic options for lighting control: DALI-2.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser.

Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.

Luminaire luminous flux: 991lm Luminaire connected power: 13.3 W Luminaire efficiency: 75 lm/W Light source luminous flux: 1140lm Light source power: 12.2 W Constant Current: 350 mA

CRI: >90

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 21° **LOR:** 87%

Average Service Life: 50000h LED reliability: >50000h L90B10

UGR: <19

Photobiological safety group: 1

This product contains a light source of energy efficiency class F

Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 01.05.2024]

5 years guarantee



Spain

T. +34 93 881 37 13

^{*}Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.