

### 152BSQ.1-R872



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Square design with frameless appearance in 203mm x 203mm.

Tilt version, adjustable to 30°.

Aluminium interior frame powder painted in assorted finishes, customized RAL under request.

To complete the effect of this fixture, it is suggested that the interior frame be painted the same RAL colour as the ceiling.

Aluminium interior reflector available in assorted finishes: faceted metalized or sandblasted metalized depending on the beam angle outcome.

Remote driver supplied.

Electronic options for lighting control: DALI-2.


The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.

3 hours battery available as option (class I).

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted using galvanised steel support with screws.

- Luminaire luminous flux:** 2075lm
- Luminaire connected power:** 18.33 W
- Luminaire efficiency:** 113 lm/W
- Light source luminous flux:** 2280lm
- Light source power:** 17 W
- Constant Current:** 500 mA
- CRI:** >90
- Colour Temperature:** 2700K
- Chromaticity Tolerance:** MacAdam 3
- Beam Angle:** 24°
- LOR:** 91%
- Average Service Life:** 50000h
- LED reliability:** 50000h L90B10
- UGR:** <16
- Photobiological safety group:** 1
- Cd/Klm:** 3580
- Imax:** 8162 Cd
- This product contains a light source of energy efficiency class E**



#### Electronic Equipment


- K:** On/Off (basic)
- S:** On/Off (AC/DC + looping through)
- SE:** On/Off (AC/DC+looping) + 3h battery
- D:** DALI-2/switchDIM/corridorFUNCTION
- DE:** DALI-2/switchDIM/corridorFUNCTION + Battery 3h
- B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

#### Finishes

**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 09.05.2025]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

#### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

#### Contact

T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)